

# Angle Grinders

Longtime best selling NPK angle grinders for various industrial applications.

## Standard Model / Non Governor

### 100mm(4") / Grip



NAG-1F-04

### 100mm(4") / Safety Lever



NAG-1FLW-04

### 125mm(5") / Grip



NAG-1F-05


### 125mm(5") / Safety Lever



NAG-1FLW-05

#### Safety Lever Type

- ① Slide the stopper.
- ② Push down the lever.



## Full Spec Model / Non Governor

### 100mm(4") / Safety lever



NAG-11A-04




### 125mm(5") / Safety lever



NAG-11A-05

\* Inch spindle type is also available.

#### Features

- Rear exhaust. 
- Quick wheel change with spindle lock. 
- Right / left replaceable handle. 



## Heavy-duty / Build-in Governor

### 100mm(4") / Safety Grip

NGP-100



### 125mm(5") / Safety Grip

NGP-125



Wheel not included.

Model	Code	Capacity (Wheel size)		Spindle thread	Max.free speed	Overall length		Height		Mass		Max. output		Air inlet thread	Hose size		Average air consumption	
		mm	in			mm	in	mm	in	kg	lb	kw	ps		RC / NPT	mm	in	m <sup>3</sup> /min
NAG-1F-04	15324	100x6x15.9	4x <sup>1</sup> / <sub>4</sub> x <sup>9</sup> / <sub>16</sub>	-	12700	190	7 <sup>1</sup> / <sub>2</sub>	83	3 <sup>1</sup> / <sub>4</sub>	1.6	3.5	0.87	1.19	1/4	9.5	3/8	0.68	24
NAG-1FLW-04	15319	100x6x15.9	4x <sup>1</sup> / <sub>4</sub> x <sup>5</sup> / <sub>8</sub>	-	12700	232	9 <sup>1</sup> / <sub>8</sub>	79	3 <sup>1</sup> / <sub>8</sub>	1.5	3.3	0.87	1.19	1/4	9.5	3/8	0.68	24
NAG-1F-05	15331	125x6x22	5x <sup>1</sup> / <sub>4</sub> x <sup>7</sup> / <sub>8</sub>	-	12700	187	7 <sup>3</sup> / <sub>8</sub>	77	3 <sup>1</sup> / <sub>16</sub>	1.5	3.3	0.87	1.19	1/4	9.5	3/8	0.68	24
NAG-1FLW-05	15326	125x6x22	5x <sup>1</sup> / <sub>4</sub> x <sup>7</sup> / <sub>8</sub>	-	12000	232	9 <sup>1</sup> / <sub>8</sub>	83	3 <sup>1</sup> / <sub>4</sub>	1.6	3.5	0.87	1.19	1/4	9.5	3/8	0.68	24
NGP-100	15239	100x6x15	4x <sup>1</sup> / <sub>4</sub> x <sup>9</sup> / <sub>16</sub>	-	13600	225	7 <sup>7</sup> / <sub>8</sub>	97	3 <sup>13</sup> / <sub>16</sub>	1.8	3.7	1.2	1.63	3/8	9.5	3/8	1.0	35.3
NGP-125	15318	125x6x22	5x <sup>1</sup> / <sub>4</sub> x <sup>7</sup> / <sub>8</sub>	-	10900	225	7 <sup>7</sup> / <sub>8</sub>	105	4 <sup>1</sup> / <sub>8</sub>	1.9	4.2	1.2	1.63	3/8	9.5	3/8	1.0	35.3

## Compact & Lightweight / Build-in Governor

### 100mm(4") / Safety Grip

NGS-100



## Build-in Governor

### 100mm(4") / Safety Grip

NAG-400A



Optional left handle.

Wheel not included.

Model	Code	Capacity (Wheel size)		Spindle thread	Max.free speed	Overall length		Height		Mass		Max. output		Air inlet thread	Hose size		Average air consumption	
		mm	in			mm	in	mm	in	kg	lb	kw	ps		RC / NPT	mm	in	m <sup>3</sup> /min
NAG-11A-04	10794	100x6x15.9	4 x <sup>1</sup> / <sub>4</sub> x <sup>5</sup> / <sub>8</sub>	-	12000	248	9 <sup>3</sup> / <sub>4</sub>	94	3 <sup>11</sup> / <sub>16</sub>	2.2	4.8	0.88	1.20	3/8	9.5	3/8	0.8	28.3
NAG-11A-05	10808	125x6x22	5 x <sup>1</sup> / <sub>4</sub> x <sup>7</sup> / <sub>8</sub>	M14 x2.0	12000	248	9 <sup>3</sup> / <sub>4</sub>	98	3 <sup>7</sup> / <sub>8</sub>	2.3	5.1	0.88	1.20	3/8	9.5	3/8	0.8	28.3
NGS-100	15208	100x6x15	4 x <sup>1</sup> / <sub>4</sub> x <sup>9</sup> / <sub>16</sub>	-	13600	192	7 <sup>9</sup> / <sub>16</sub>	85	3 <sup>3</sup> / <sub>8</sub>	1.0	2.2	0.64	0.88	1/4	9.5	3/8	0.5	17.7
NAG-400A	15320	100x6x15	4 x <sup>1</sup> / <sub>4</sub> x <sup>9</sup> / <sub>16</sub>	-	13600	216	8 <sup>1</sup> / <sub>2</sub>	86	3 <sup>3</sup> / <sub>8</sub>	1.7	3.7	0.85	1.15	1/4	9.5	3/8	0.65	23