

Straight Grinders

- Heavy duty and powerful grinders with narrow aluminium housing.
- Ideal for operation in limited work space.

■ Safety Grip Type

● 65mm(2 1/2") Built-in governor



NHG-65D



NHG-65LD



NHG-65LD-75

● 32mm (1 1/4") Without governor



NHG-65K-06 (6mm collet)
NHG-65K-20 (1/4" collet)

*3mm & 1/8" collets also available.



NHG-65LK-06 (6mm collet)
NHG-65LK-20 (1/4" collet)


*3mm & 1/8" collets also available.



NHG-65LK-75 (6mm collet)

Safety Grip Type

- ① Pull back the sleeve, and
- ② Turn it anticlockwise to start.



● 100mm(4") Built-in governor



NHG-100A

● 125mm(5") Built-in governor



NHG-125

● 150mm(6") Built-in governor



NHG-150

Rear exhaust type




NHG-65K-BE (6mm collet)

Straight Grinders

Safety Lever Type

- ① Slide the stopper.
- ② Push down the lever.



■ Safety Lever Type

● 65mm(2 1/2") Built-in governor



NHG-65DLW



NHG-65LDLW

● 32mm (1 1/4") Non governor



NHG-65KLW-06 (6mm collet)
NHG-65KLW-20 (1/4" collet)

*3mm & 1/8" collets also available.

*Rear exhaust type is also available.
Model: NHG-65KLW-BE (6 mm collet)

● 100mm(4") Built-in governor



NHG-100ALW

● 125mm(5") Built-in governor



NHG-125LW

● 150mm(6") Built-in governor



NHG-150LW



NHG-65LKLW-06 (6mm collet)
NHG-65LKLW-20 (1/4" collet)

*3mm & 1/8" collets also available.

Model	Code	Collet size	Capacity (Wheel size)		Max.free speed	Overall length		Mass		Max. output		Air inlet thread	Hose size		Average air consumption	
			mm/in	mm		in	mm	in	kg	lb	kw		ps	Rc or NPT	mm	in
NHG-65D	10053	-	65x13x9.5	2 ⁹ / ₁₆ x 1/2 x 3/8	14600	310	12 ³ / ₁₆	1.3	2.9	0.58	0.79	1/4	9.5	3/8	0.55	19.4
NHG-65LD	10054	-	65x13x9.5	2 ⁹ / ₁₆ x 1/2 x 3/8	14600	510	20 ¹ / ₁₆	1.6	3.5	0.58	0.79	1/4	9.5	3/8	0.55	19.4
NHG-65LD-75	70427	-	65x13x9.5	2 ⁹ / ₁₆ x 1/2 x 3/8	14600	756	29 ³ / ₄	2.2	4.8	0.58	0.79	1/4	9.5	3/8	0.55	19.4
NHG-100A	10075	-	100x19x12.7	4 x 3/4 x 1/2	9500	366	14 ⁵ / ₁₆	2.3	5.1	0.88	1.2	3/8	12.7	1/2	0.65	23.0
NHG-125	10077	-	125x19x12.7	5 x 3/4 x 1/2	7500	405	15 ¹⁵ / ₁₆	3.2	7.0	1.04	1.42	3/8	12.7	1/2	0.9	31.8
NHG-150	10081	-	150x25x15.9	6 x 1 x 5/8	6200	440	17 ³ / ₁₆	4.6	10.1	1.32	1.8	3/8	12.7	1/2	1.1	38.8
NHG-65K-06	10650	6mm	32	1 1/4	18000	311	12 1/4	1.3	2.9	0.58	0.79	1/4	9.5	3/8	0.55	19.4
NHG-65K-20	10061	1/4"														
NHG-65K-BE	15321	6mm	32	1 1/4	18000	359	14 1/7	1.5	3.3	0.58	0.79	1/4	9.5	3/8	0.55	19.4
NHG-65LK-06	10066	6mm	32	1 1/4	18000	511	20 1/8	1.6	3.5	0.58	0.79	1/4	9.5	3/8	0.55	19.4
NHG-65LK-20	10069	1/4"														
NHG-65LK-75	70430	6mm	32	1 1/4	18000	756	29 ³ / ₄	2.2	4.8	0.58	0.79	1/4	9.5	3/8	0.55	19.4

Model	Code	Collet size	Capacity (Wheel size)		Max.free speed	Overall length		Mass		Max. output		Air inlet thread	Hose size		Average air consumption	
			mm/in	mm		in	mm	in	kg	lb	kw		ps	Rc or NPT	mm	in
NHG-65DLW	10055	-	65x13x9.5	2 ⁹ / ₁₆ x 1/2 x 3/8	14600	338	13 ⁵ / ₁₆	1.3	2.9	0.58	0.79	1/4	9.5	3/8	0.55	19.4
NHG-65LDLW	10056	-	65x13x9.5	2 ⁹ / ₁₆ x 1/2 x 3/8	14600	538	21 ³ / ₁₆	1.6	3.5	0.58	0.79	1/4	9.5	3/8	0.55	19.4
NHG-100ALW	10076	-	100x19x12.7	4 x 3/4 x 1/2	9500	411	16 ³ / ₁₆	2.3	5.1	0.88	1.2	3/8	12.7	1/2	0.65	23.0
NHG-125LW	10078	-	125x19x12.7	5 x 3/4 x 1/2	7500	452	17 ¹³ / ₁₆	3.2	7.0	1.04	1.42	3/8	12.7	1/2	0.9	31.8
NHG-150LW	10082	-	150x25x15.9	6 x 1 x 5/8	6200	486	19 ¹ / ₈	4.6	10.1	1.32	1.8	3/8	12.7	1/2	1.1	38.8
NHG-65KLW-06	10062	6mm	32	1 1/4	18000	339	13 3/4	1.3	2.9	0.58	0.79	1/4	9.5	3/8	0.55	19.4
NHG-65KLW-20	10065	1/4"														
NHG-65KLW-BE	15334	6mm	32	1 1/4	18000	359	14 1/7	1.5	3.3	0.58	0.79	1/4	9.5	3/8	0.55	19.4
NHG-65LKLW-06	10070	6mm	32	1 1/4	18000	539	21 1/4	1.6	3.5	0.58	0.79	1/4	9.5	3/8	0.55	19.4
NHG-65LKLW-20	10073	1/4"														