

New Kelens / Stone Scraper

New Kelens

- Long scalers for removal of scales, rust, and dirt.
- Ideal for removing scale and rust of ships or concrete dress in mixer agitators.
- 1 chisel is included (length 200 mm / width 38 mm).



**NNK-250
NNK-250L**



**NNK-500
NNK-500L**




**NNK-1000
NNK-1000L**



L: Lever Type


Chisels for New Kelens

● Width 38mm



Length mm (L)	Code No.
200	17510080
300	17300676

● Width 60mm



Length mm (L)	Code No.
200	17510100
300	17300689

Model	Code	Blow per minute min ⁻¹	Piston diameter		Piston stroke		Overall length		Mass		Air inlet thread Rc or NRT	Hose size		Average air consumption	
			mm	in	mm	in	mm	in	kg	lb		mm	in	m ³ /min	ft ³ /min
NNK-250	30306	4000	25.4	1	23	7/8	514	20 ¹ / ₄	3.4	7.5	3/8	9.5	3/8	0.45	15.9
NNK-250L	30337	4000	25.4	1	23	7/8	571	22 ¹ / ₂	4.5	9.9	3/8	9.5	3/8	0.45	15.9
NNK-500	30045	4000	25.4	1	23	7/8	754	29 ¹¹ / ₁₆	4.2	9.2	3/8	9.5	3/8	0.45	15.9
NNK-500L	30335	4000	25.4	1	23	7/8	801	31 ⁹ / ₁₆	5.3	11.7	3/8	9.5	3/8	0.45	15.9
NNK-1000	30046	4000	25.4	1	23	7/8	1284	50 ⁹ / ₁₆	5.8	12.8	3/8	9.5	3/8	0.45	15.9
NNK-1000L	30336	4000	25.4	1	23	7/8	1341	52 ¹³ / ₁₆	6.9	15.2	3/8	9.5	3/8	0.45	15.9

Stone Scraper

- Designed for roughing concrete and stone.
- Powerful and light.
- Rubber handles reduce vibration.



NB-10A

Scraper Heads (Option)

9 Teeth	16 Teeth	25 Teeth	36 Teeth
17511270	17511280	17511290	17511300

Model	Code	Blow per minute min ⁻¹	Height		Mass		Air inlet thread Rc or NRT	Hose size		Average air consumption	
			mm	in	kg	lb		mm	in	m ³ /min	ft ³ /min
NB-10A	30400	2500	210	8 1/4	10	22	3/8	9.5	3/8	0.35	12.4

Sand Rammers / Scaling Hammers

Sand Rammers

- Ideal tools for compacting sand molds and firebricks.
- Please specify butt type; rubber or steel.

**B-00A(R)
B-00A(S)**



**F-00(R)
F-00(S)**



**B-0A(R)
B-0A(S)**



**F-0(R)
F-0(S)**



**B-1A(R)
B-1A(S)**



**F-1(R)
F-1(S)**



**(R): Rubber butt
(S): Steel butt**



Steel butt

**F-2(R)
F-2(S)**



**F-4(R)
F-4(S)**



Model	Code	Piston diameter		Piston stroke		Overall length		Mass		Butt diameter		Air inlet thread Rc or NRT	Hose size		Average air consumption	
		mm	in	mm	in	mm	in	kg	lb	mm	in		mm	in	m ³ /min	ft ³ /min
B-00A(R)	30028	18	5/16	60	2 ³ / ₈	337	13 ¹ / ₄	2.1	4.6	40	1 ⁹ / ₁₆	1/4	9.5	3/8	0.2	7.1
B-0A(R)	30030	22	7/8	60	2 ³ / ₈	380	14 ¹⁵ / ₁₆	3.1	6.8	50	2	1/4	12.7	1/2	0.25	8.8
B-1A(R)	30032	25.4	1	110	4 ⁵ / ₁₆	502	19 ³ / ₄	5.4	11.9	64	2 ¹ / ₂	3/8	12.7	1/2	0.4	14.1
F-00(R)	30017	18	11/16	60	2 ³ / ₈	390	15 ³ / ₈	2.1	4.6	40	1 ⁹ / ₁₆	3/8	9.5	3/8	0.2	7.1
F-0(R)	30019	22	7/8	60	2 ³ / ₈	435	17 ¹ / ₈	3.1	6.8	50	2	3/8	12.7	1/2	0.25	8.8
F-1(R)	30021	25.4	1	110	4 ⁵ / ₁₆	1142	43 ²⁴ / ₂₅	6.8	15.0	64	2 ¹ / ₂	1/2	12.7	1/2	0.4	14.1
F-2(R)	30023	32	1 ¹ / ₄	120	4 ³ / ₄	1204	44 ² / ₅	9.0	19.8	70	2 ³ / ₄	1/2	12.7	1/2	0.55	19.4
F-4(R)	30025	40	1 ⁹ / ₁₆	120	4 ³ / ₄	1209	47 ³ / ₅	12.0	26.4	87	3 ⁷ / ₁₆	1/2	12.7	1/2	0.85	30

Scaling Hammers

- Suitable for surfacing concrete and stone.



**S-2A, S-2A(C)
S-2AL, S-2AL(C)**

L: Lever Type



**MS-30, MS-30(C)
MS-30L, MS-30L(C)**

L: Lever Type

(C): Carbide tipped piston type

Model	Code	Blow per minute min ⁻¹	Piston diameter		Piston stroke		Overall length		Height		Mass		Air inlet thread Rc or NRT	Hose size		Average air consumption	
			mm	in	mm	in	mm	in	mm	in	kg	lb		mm	in	m ³ /min	ft ³ /min
S-2A	30036	3500	30	1 ³ / ₁₆	15	9/16	490	19 ⁵ / ₁₆	100	3 ¹⁵ / ₁₆	2.1	4.6	3/8	9.5	3/8	0.4	14.1
S-2A(C)	30037										2.7	5.9					
S-2AL	30332	3500	30	1 ³ / ₁₆	15	9/16	496	19 ¹ / ₂	100	3 ¹⁵ / ₁₆	2.7	5.9	3/8	9.5	3/8	0.4	14.1
S-2AL(C)	30355										3.2	7.0					
MS-30	30051	7000	22	7/8	10	3/8	326	12 ¹³ / ₁₆	86	3 ³ / ₈	3.2	7.0	3/8	12.7	1/2	0.55	19.4
MS-30(C)	30052										3.8	8.4					
MS-30L	30333	7000	22	7/8	10	3/8	332	13 ¹ / ₁₆	86	3 ³ / ₈	3.8	8.4	3/8	12.7	1/2	0.55	19.4
MS-30L(C)	30401																