

CNS Grinders

- Ideal for fine finish work and removal of block scale, oxide layer, or paint.



■ Safety Grip Type



NHG-65G



NHG-75G

■ Optional CNC Grinding Wheels			
	Model	CNS Wheel / Size	Code No.
	NHG-65G	Uni Wheel Type 65x13 (mm) 2 ⁹ / ₁₆ x1 ¹ / ₂ (inch)	24906005
	NHG-75G	Disc Type 100x13 (mm) 4x1 ¹ / ₂ (inch)	24906003

Model	Code	Capacity (Wheel size)		Max.free speed min ⁻¹	Overall length		Height		Mass		Max. output		Airinlet thread Rc or NPT	Hose size		Average air consumption	
		mm	in		mm	in	mm	in	kg	lb	kw	ps		mm	in	m ³ /min	ft ³ /min
NHG-65G	10044	65x26x9.5	2 ¹ / ₂ x1 x ³ / ₈	14000	310	12 ³ / ₁₆	-	-	1.3	2.9	0.58	0.79	1/4	9.5	3/8	0.55	19.4
NHG-75G	10074	100x26x9.5	4 x ¹ / ₄ x ⁵ / ₈	6000	328	12 ¹⁵ / ₁₆	-	-	1.7	3.7	0.77	1.05	1/4	9.5	3/8	0.45	15.9

Wire Brush Sanders

- Ideal for removing rust and paint, and descaling beads after welding.

■ Safety Grip Type



NAG-70WA

■ Safety Lever Type



NAG-70WALW

Model	Code	Capacity (Wheel size)		Max.free speed min ⁻¹	Overall length		Height		Mass		Max. output		Airinlet thread Rc or NPT	Hose size		Average air consumption	
		mm	in		mm	in	mm	in	kg	lb	kw	ps		mm	in	m ³ /min	ft ³ /min
NAG-70WA	10744	120x22	4 ³ / ₄ x ⁷ / ₈	6500	257	10 ¹ / ₈	109	4 ⁵ / ₁₆	2.8	6.2	1.2	1.6	3/8	12.7	1/2	0.9	31.8
NAG-70WALW	10714	120x22	4 ³ / ₄ x ⁷ / ₈	6500	276	10 ⁷ / ₈	109	4 ⁵ / ₁₆	2.8	6.2	1.2	1.6	3/8	12.7	1/2	0.9	31.8

Comfortable, compact, and perfectly balanced sanders for finishing.

■ Lever Type

● 100mm(4")



NSG-100

■ Grip Type

● 125mm(5")



NSG-125

■ Safety Grip Type

● 150mm(6")



NSG-150X

■ Safety Grip Type

● 180mm(7")



NSG-180XC

■ Safety Lever Type

● 180mm(7")



NSG-180XCLW

Safety Grip

- ① Pull back the sleeve.
- ② Turn it anticlockwise.



Safety Lever

- ① Slide up the stopper.
- ② Push down the lever.



Model	Code	Capacity (Wheel size)		Max.free speed min ⁻¹	Overall length		Height		Mass		Airinlet thread Rc or NPT	Hose size		Average air consumption	
		mm	in		mm	in	mm	in	kg	lb		mm	in	m ³ /min	ft ³ /min
NSG-100	10176	100x16	4 x ⁵ / ₈	13000	161	6 ⁵ / ₁₆	102	4	0.9	2.0	1/4	6.3	1/4	0.4	14.1
NSG-125	15313	125x16	5 x ⁷ / ₈	11000	190	7 ¹ / ₂	190	7 ¹ / ₂	1.5	3.3	1/4	9.5	3/8	0.65	23.0
NSG-150X	15309	150x22	6 x ⁷ / ₈	8400	209	8 ¹ / ₄	179	7 ¹ / ₁₆	2.2	4.8	3/8	12.7	1/2	0.65	23.0
NSG-180XC	15307	180x22	7 x ⁷ / ₈	7600	209	8 ¹ / ₄	179	7 ¹ / ₁₆	2.2	4.8	3/8	12.7	1/2	0.65	23.0
NSG-180XCLW	15308	180x22	7 x ⁷ / ₈	7600	239	9 ⁷ / ₁₆	190	8 ¹ / ₂	2.4	5.3	3/8	12.7	1/2	0.65	23.0