

# Chain Tongs



## CHAIN TONGS

- Designed and sized to provide extra leverage for the toughest jobs.
- All models feature double-end jaw styles that can be reversed, except Model 3215, which is a single-end tong.

| Catalog No. | Model No. | Description            | Total Length |       | Pipe Capacity |           | Chain Length | Chain Length | Chain Breaking Load |        | Weight |    | Std. Pack |
|-------------|-----------|------------------------|--------------|-------|---------------|-----------|--------------|--------------|---------------------|--------|--------|----|-----------|
|             |           |                        | in.          | mm    | in.           | mm        | in.          | mm           | lb.                 | kg     | lb.    | kg |           |
| 92665       | 3229      | Double-End Chain Tongs | 27           | 686   | ¼ - 2 ½       | 6 - 65    | 17 ½         | 445          | 13,800              | 6,260  | 11     | 5  | 1         |
| 92670       | 3231      |                        | 37           | 939   | ¾ - 4         | 20 - 100  | 22 ½         | 572          | 17,600              | 7,983  | 21     | 10 |           |
| 92675       | 3233      |                        | 44           | 1,117 | 1 - 6         | 25 - 150  | 32           | 813          | 20,100              | 9,117  | 29     | 13 |           |
| 92680       | 3235      |                        | 50           | 1,270 | 1 ½ - 8       | 40 - 200  | 40 ½         | 1,29         | 22,000              | 9,979  | 39     | 18 |           |
| 92685       | 3237      |                        | 64           | 1,625 | 2 - 12        | 50 - 300  | 55 ½         | 1,410        | 31,000              | 14,061 | 67     | 30 |           |
| 92660       | 3215      | Single-End Chain Tongs | 87           | 2,209 | 4 - 18        | 100 - 450 | 74 ½         | 1,892        | 56,000              | 25,401 | 156    | 71 |           |

# Strap Wrenches



## STRAP WRENCHES

- Strap Wrenches are best for any polished pipe.
- Strong, woven nylon strap gives tight grip.
- Two models available with special strap for plastic pipe.\*

## REPLACEMENT STRAPS

| Replac. Strap | Strap Length |       | Strap Width |    |
|---------------|--------------|-------|-------------|----|
|               | in.          | mm    | in.         | mm |
| 31990         | 17           | 425   | ½           | 12 |
| 32015         |              |       | 1 ⅝         | 30 |
| 32020         | 30           | 760   | 1 ⅝         | 30 |
| 32025         | 24           | 600   | 1 ⅝         | 30 |
| 32035*        | 17           | 425   | 1 ⅞         | 27 |
| 32050         | 29 ¼         | 750   | 1 ¾         | 45 |
| 32055         | 48           | 1,200 | 1 ¾         | 45 |
| 32065*        | 29 ¼         | 750   | 1 ¾         | 45 |

| Catalog No. | Model No. | Description  | Handle Length |      | Strap Length |     | Strap Width |    | Pipe Capacity | Pipe Capacity | Actual O.D. Capacity | Actual O.D. Capacity | Weight |     | Std. Pack |
|-------------|-----------|--------------|---------------|------|--------------|-----|-------------|----|---------------|---------------|----------------------|----------------------|--------|-----|-----------|
|             |           |              | in.           | mm   | in.          | mm  | in.         | mm |               |               | in.                  | mm                   | lb.    | kg  |           |
| 31335       | 1         | Strap Wrench | 11 ¾          | 300  | 17           | 425 | ½           | 12 | 2             | 50            | 3 ½                  | 90                   | 1 ¼    | 0.5 | 1         |
| 31340       |           |              |               |      |              |     | 1 ⅝         | 30 | 2             | 50            | 3 ½                  | 90                   | 1 ¾    | 0.8 |           |
| 31345       | 2         |              |               |      |              |     | 1 ⅝         | 30 | 2             | 50            | 5 ½                  | 135                  |        |     |           |
| 31350       |           |              |               |      |              |     | 1 ⅝         | 30 | 2             | 50            | 5 ½                  | 135                  |        |     |           |
| 31355       | 2P        |              |               |      |              |     | 1 ⅞         | 27 | 2             | 50            | 3 ½                  | 90                   |        |     |           |
| 31360       | 5         | 18           | 450           | 29 ¼ | 750          | 1 ¾ | 45          | 5  | 125           | 7             | 175                  | 2                    | 0.9    |     |           |
| 31365       |           |              |               | 48   | 1,200        | 1 ¾ | 45          | 5  | 125           | 12            | 300                  |                      |        |     |           |
| 31370       | 5P        |              |               | 29 ¼ | 750          | 1 ¾ | 45          | 5  | 125           | 5 ½           | 135                  | 2 ⅞                  | 1.0    |     |           |

Rated pipe capacity= nominal diameter that can be correctly tightened  
 Actual O.D. Capacity = actual O.D. that chain can accommodate  
 \* Strap designed for use with plastic pipe

# Adjustable Wrenches



## ADJUSTABLE WRENCHES

- High-grade alloy steel.
- Nickel based plating with brushed finish to reduce rust and corrosion.
- Forged and heat-treated for durability.
- Jaw scales in SAE and metric for quick adjustment.

| Catalog No. | Model No. | Description           | Nom. Size |     | Jaw Opening |    | Weight |     | Std. Pack |
|-------------|-----------|-----------------------|-----------|-----|-------------|----|--------|-----|-----------|
|             |           |                       | in.       | mm  | in.         | mm | lb.    | kg  |           |
| 86902       | 756       | 6" Adjustable Wrench  | 6         | 150 | ¾           | 20 | ¼      | 0.1 | 5         |
| 86907       | 758       | 8" Adjustable Wrench  | 8         | 200 | 7/8         | 22 | ½      | 0.2 |           |
| 86912       | 760       | 10" Adjustable Wrench | 10        | 250 | 1 ⅝         | 30 | ¾      | 0.3 |           |
| 86917       | 762       | 12" Adjustable        | 12        | 300 | 1 ⅞         | 35 | 1 ½    | 0.6 | 4         |
| 86922       | 765       | 15" Adjustable        | 15        | 375 | 1 11/16     | 40 | 3      | 1.3 |           |
| 86927       | 768       | 18" Adjustable        | 18        | 450 | 2 ⅞         | 50 | 5 ⅞    | 2.3 | 1         |
| 86932       | 774       | 24" Adjustable        | 24        | 600 | 2 7/16      | 60 | 9 ¼    | 4.2 |           |