

Threading Accessories



*Flip top included with every quart bottle.

**FBC™ System Compatible indicates that this product has been tested and is monitored on an ongoing basis to assure chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings.

FlowGuard Gold®, BlazeMaster®, Corzan® and FBC™ are trademarks of The Lubrizol Corporation. FBC™ is a trademark of The Lubrizol Corporation.

***Aerosol can.

THREAD CUTTING OIL

RIDGID® thread cutting oils are free of chlorine and other halogens, PCBs and heavy metals. Complete material safety data sheet available.

- Cools threads and pipe during operation.
- Speeds metal removal.
- Improves thread quality.
- Reduces threading torque.

Feature	Dark	Nu-Clear	Endura-Clear	Extreme Performance
Low Odor	•	•	•	•
Anti-Mist Formulation	•	•	•	•
Extended Die Life			•	•
FBC™ System Compatible**			•	
Designed for Stainless Steel				•
Working Viscosity	0°F	-20°	-20°	0°

Catalog No.	Model No.	Description	Container Size	Container Size	Containers Per Case	Weight Per Case	
			gal	l		lb.	kg
41590*			0.2	0.9	12	22	10
70830		Dark	1	3.8	6	50	23
41600		Dark	5	18.9	1	42	19
41610		Dark	55	207.9	1	465	221
70835		Nu-Clear	1	3.8	6	50	23
41575		Nu-Clear	5	18.9	1	42	19
41585		Nu-Clear	55	207.9	1	465	211
32808**		Endura-Clear	1	3.8	6	50	23
74012		Extreme Performance	1	3.8	6	50	23
74047		Extreme Performance	5	18.9	1	42	19
76767		Extreme Performance	55	207.9	1	465	211
22088		Extreme Performance Aerosol	0.1	0.4	12	12	6
11931***		Thread Cutting Oil	1.1	5	4	51	23



SPECIFICATIONS

- Chip pan diameter—14 1/4 in.
- Chip pan depth—8 3/4.
- Hose length—55 in.
- Capacity—1 gallon.

MODEL 418 OILER

The Model 418's durable pump assembly and heavy-duty reservoir are designed to increase productivity.

- Pump assembly provides 50% more oil per stroke than other hand-held oilers for longer die life.
- An ergonomic 2-finger trigger design that reduces user fatigue.
- Die cast, heavy-duty body with swivel nozzle with no exposed parts for longer life.
- The 418 oiler features a patent pending fastener-less twist and lock drip pan that easily locks in place.
- The material withstands abrasion, is lighter than metal and does not rust.
- The reservoir will not crack or leak.
- Material is so strong that under normal use, no dents will form on impact or shape changes will occur over time. As a result, the drip pan will fit squarely on the reservoir time after time.
- Integral molded body eliminates leaks at the hose-reservoir connection.
- Convenient anti-slip grip design with integral hood for easy hanging.

Catalog No.	Model No.	Description	Weight	
			lb.	kg
10883	418	Oiler with One Gallon Premium Thread Cutting Oil	20 ½	9.4
72342	402	Hand operated oiler with attachment for 1 gallon and 5 gallon containers and 54" hose.	2 ½	1.2
72332	#4	Hand-operated oiler only	1 ¼	0.5
72327		Hand-operated oiler with 54" hose and fittings	2 ¼	1

See page 4.12

